

| Model | TR10-1310C | |
|------------------------|--|----------------------------|
| Payload | 10kg | |
| Arm Reach | 1310mm | |
| DOF | 6 | |
| Power Supply | 690~264VAC,47~63Hz/48VDC | |
| Programming | Drag teaching, graphic pages | |
| Security Module | More than 20 adjustable safety features including collision detection, virtual wall and collaboration mode | |
| Certification | EN ISO13849-1, Cat.3, EN ISO10218-1, European Union CE certification | |
| Position Repeatability | ±0.05mm | |
| Protection Rating | IP54/IP67 | |
| Max Speed | J1 | 120°/s |
| | J2 | 120°/s |
| | J3 | 120°/s |
| | J4 | 180°/s |
| | J5 | 180°/s |
| | J6 | 180°/s |
| Max Operation Area | J1 | ±175° |
| | J2 | ±175° |
| | J3 | -245°~65° |
| | J4 | ±175° |
| | J5 | ±175° |
| | J6 | ±360° |
| Noise Level | Laeq ≤ 85dB(A) | |
| Rated Power | 3.5Kw | |
| Applicable Environment | Temperature | 0~45°C |
| | Humidity | 20%~80%RH(No Condensation) |
| Body Weight | 43Kg | |
| Control Cabinet | TRC5-G06 | |
| Installation Method | Installation at Any Angle | |